

Roulement à bille simple rangée 3005-DS-NICE - 3005-DS-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/3005-ds-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- WYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|---------|-------------|-------------|---------------|---------------|------|------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3005™ | | | DS | | | +0.005 +0.13 -0.000 -0.00 | +0.000 +0.00 -0.0005 -0.013 |
| | | | | | | 7.938 | 23.020 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|------------------------------|------------------------------|-------------------------|--------------------------------|------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lbs) (N) | STATIC Co (lbs) (N) | W O (lbs) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.3125 7.938 | 350 1558 | 300 1355 | 0.04 0.02 | 0.503 12.78 | 0.778 19.76 | 0.012 0.30 |

O Weights given are for greased and sealed versions
 O 3038 and larger +.0000/-0.005 (+.000/-0.13)

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | NICE |
| N° Ean13 | 3663952558172 |
| Diam. intérieur | 7.938 mm |
| Diam. extérieur | 23.02 mm |
| Épaisseur | 7.938 mm |
| Poids | 20 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE