


## Roulement à bille simple rangée 3014-SC-NICE - 3014-SC-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/3014-sc-nice>

**3000 Series® Semi-Ground Radial Bearings** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3014™		SC				+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.015 -0.013

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lbs) (N)	STATIC Co (lbs) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.3750 9.525	600 2670	475 2114	0.06 0.03	0.585 15.11	1.014 25.76	0.025 0.64

Ⓢ Weights given are for greased and sealed versions  
Ⓢ 3038 and larger +0.000/-0.006 (+0.000/-0.15)

## CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558332
Diam. intérieur	9.525 mm
Diam. extérieur	28.575 mm
Épaisseur	9.525 mm
Poids	30 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE