

Roulement à bille simple rangée 3015-NS-NICE - 3015-NS-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/3015-ns-nice>

3000 Series® Semi-Ground Radial Bearings **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|---------|-------------|-------------|---------------|---------------|------|------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3015™ | | | | | NS | +0.005 +0.13 -0.000 -0.00 | +0.000 +0.00 -0.0005 -0.013 |
| | | | | | | 0.4375 11.113 | 1.1250 28.575 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|------------------------------|------------------------------|-------------------------|--------------------------------|------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lbs) (N) | STATIC Co (lbs) (N) | W ⓪ (lbs) (kg) | da min (in) (mm) | Da max (in) (mm) | r max (in) (mm) |
| 0.3750 9.525 | 600 2670 | 475 2114 | 0.06 0.03 | 0.622 15.80 | 1.014 25.76 | 0.025 0.64 |

⓪ Weights given are for greased and sealed versions
⓪ 3015 and larger +0.0005/-0.005 (+0.001/-0.13)

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | NICE |
| N° Ean13 | 3663952558394 |
| Diam. intérieur | 11.113 mm |
| Diam. extérieur | 28.575 mm |
| Épaisseur | 9.525 mm |
| Poids | 30 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE