


## Roulement à bille simple rangée 3030-DS-NICE - 3030-DS-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/3030-ds-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
						+0.005 +0.13 -0.000 -0.000	+0.000 +0.00 -0.0005
3030™			DS			0.7500 19.050	1.5250 41.275

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C <sub>0</sub> (lb) (N)	W <sup>0</sup> (lb) (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5795	1010 4485	0.16 0.07	0.965 24.51	1.446 36.73	0.025 0.64

<sup>0</sup> Weights given are for greased and sealed versions  
<sup>0</sup> 3030 and larger +0.0005/-0.0005 (+0.001/-0.013)

## CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558677
Diam. intérieur	19.05 mm
Diam. extérieur	41.275 mm
Épaisseur	12.7 mm
Poids	70 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE