

Roulement à bille simple rangée 3033-DS-NICE - 3033-DS-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/3033-ds-nice>

3000 Series® Semi-Ground Radial Bearings (con't) NICE

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|---------|-------------|-------------|---------------|---------------|------|-------------------------------------|--------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 3033™ | | | DS | | | +0.005 +0.13 -0.000 -0.013 | +0.000 +0.00 -0.0005 -0.013 |
| | | | | | | 0.6250 15.875 | 1.7000 44.450 |

| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | |
|----------------------------|-----------------------------|---|--------------------------------|------------------------------------|------------------------------------|-----------------------|
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC C ₀ (lb) (N) | W ^⓪ (lb) (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) |
| 0.5000 12.700 | 1300 5785 | 1025 4561 | 0.22 0.10 | 0.845 21.46 | 1.530 38.86 | 0.025 0.64 |

^⓪ Weights given are for greased and sealed versions
^⓪ 3038 and larger +0.0005/-0.005 (+0.002/-0.13)

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | NICE |
| N° Ean13 | 3663952558721 |
| Diam. intérieur | 15.875 mm |
| Diam. extérieur | 44.45 mm |
| Épaisseur | 12.7 mm |
| Poids | 100 g |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE