


Roulement à bille simple rangée 3038-SS-NICE - 3038-SS-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/3038-ss-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3038™				SS		+0.005 +0.13 -0.000 -0.005	+0.000 +0.50 -0.005 -0.013
						0.7500 19.050	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC C ₀ (lb) (N)	W [⊕] (lb) (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.9625 14.288	1480 6598	1350 6008	0.32 0.15	0.988 25.10	1.760 44.70	0.035 0.89

[⊕] Weights given are for greased and sealed versions
[⊖] 3038 and larger +.0000/-0.005 (+.000/-0.13)

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952558813
Diam. intérieur	19.05 mm
Diam. extérieur	50.8 mm
Épaisseur	14.288 mm
Poids	150 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE