

Rotule TSM MS-M25-20-DUNLOP - MS-M25-20-DUNLOP

https://www.123roulement.be/roulement-palier/rotule/tsm/ms-m25-20-dunlop

MALE ROD ENDS 



MS SERIES: MS - MSS - MS SS

Description:
MS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 520M4779p and forged 980M44, zinc plated and clear trivalent passivate and stainless steel 303, and forged 304. Inner Ring: Steel 070M20 zinc plated and clear trivalent passivate. Liner: High strength PTFE bronze mesh composite. Ball: Bearing steel 100Cr6, heat treated, polished & electroless nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, high shock loads, extended wear life, no maintenance, studed and stainless steel options.

Possible Applications:
Medium/heavy industrial mechanical applications, construction equipment, agricultural equipment, motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-20°C to +250°C

Specification:
ELV & RoHS compliant

Housing: Steel 520M4779p (Steel MS - M12) Forged 980M44 (Stainless Steel - MSS) Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate

Ball: Bearing Steel 100Cr6, Case Hardened and Electroless Nickel Plated

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	Static Load Rating (Newtons) Radial
MS-M25-20		20	M24x2.00	31	22.00	60	94	57	29.60	60,900

Interchange table

Dunlop	Rose	Aurora	Askubal	SKF	ASAHI	IKO	Fluro
MS-M (metric)	MNC	MM-M-T and MB-M-T	Ka-P	SAKB-P	JAM-EC	POS-EC	GASW
MS (imperial)	RMC	MM-T and MB-T	-	-	-	POSB-EC	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

For stainless steel add 'SS' to part no. For example 'MS-M05 SS'

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3663952559582
Diam. intérieur	20 mm
Diam. extérieur	60 mm
Epaisseur	31 mm
Type	TSM
Filetage	Filetage à droite
Lubrification	sans
Charge statique	0.0609 kN
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE