


## Roulement à bille simple rangée 400-36V-NICE - 400-36V-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/400-36v-nice>

**400** Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm)	B O.D. (in) (mm)	C WIDTH (in) (mm)	D WIDTH (in) (mm)	No.	Size (mm)
400™	36V	0.750 0.000 0.000	1.750 +0.002/0.000 44.45	0.562 +0.010/-0.010 14.27	0.562 Reference 14.27	14	1/4 6.35

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
0.22 0.10	625 2781	430 1914	300 1335	240 1068	188 748	117 521

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

## CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560151
Diam. intérieur	19.05 mm
Diam. extérieur	44.45 mm
Épaisseur	14.27 mm
Poids	100 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE