


Roulement à bille simple rangée 5281-V-NICE - 5281-V-NICE

<https://www.123roulement.be/roulement-palier/roulement-bille/simple-rangee/5281-v-nice>

5000 Series® Single Row Unground Flanged Radial Bearings (con't) **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE HIGH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- FLANGE ON O.D. LOCATES BEARING IN TUBE OR HOUSING
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA						
		BORE		O.D.			WIDTH	
		A (in) (mm)	B (in) (mm)	C (in) (mm)	D (in) (mm)	E (in) (mm)	F (in) (mm)	G (in) (mm)
		+0.005/-0.000 +13/-00	+0.005/-0.000 +13/-00	+0.010/-0.010 +25/-25				+0.010/-0.010 +25/-25
5281™	V	0.502 12.73	1.579 40.08	0.515 13.08	0.140 3.56	1.887 42.85	0.234 5.94	0.809 15.47

BALLS (in) (mm)	W (lbs) (kg)	RADIAL CAPACITY					
		REVOLUTIONS PER MINUTE					
		50 (lbs) (N)	100 (lbs) (N)	200 (lbs) (N)	300 (lbs) (N)	600 (lbs) (N)	1200 (lbs) (N)
12	0.22 6.35	535 2381	367 1633	258 1148	206 917	144 641	100 445

Notes: Balls - Carbon Steel Grade 200 Bands - 1010 Carbon Steel, Soft
Rings - Carbon Steel, Case Hardened Bearings supplied prelubricated with grease

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3663952560298
Diam. intérieur	12.7 mm
Diam. extérieur	40.08 mm
2nd Diam. extérieur	42.85 mm
Epaisseur	13.08 mm
2nd Epaisseur	15.47 mm
Poids	100 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE