


Accessoire de palier 7609-DL-NICE - 7609-DL-NICE

<https://www.123roulement.be/roulement-palier/paliers/accessoires/7609-dl-nice>

7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring **NICE**

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE INCH DIMENSIONS
- MEDIUM LOADS
- MAX SPEED RANGE - 5000 - 8000 RPM
- THROUGH HARDENED
- GRIND BEARING
- AVAILABLE SINGLE RING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHARP FILLET RADIUS - THIS IS NOT CHANGABLE AS AN OPTION
- DIMENSIONS FOR APPLICATIONS WITH SHROUDS, SHIELDS AND RINGS



BEARING Ø	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7609™	.625 14.29	1.790 44.95	0.6250 15.88	0.0625 1.59	1.009 25.63	0.138 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Radius R (in) (mm)	Dynamic C _d (lb) (N)	Static C _s (lb) (N)	W (lb) (kg)
0.042 1.07	1.922 48.82	1.992 50.60	0.405 10.29	0.233 5.92	10-32	0.036 0.89	2996 11548	1025 4061	0.34 0.15

Ⓜ When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)
Ⓜ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear

Ⓜ Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015)
Ⓜ Weights given are for greased and sealed versions

All bearing designations listed herein are trademarks of RBC Nide® Bearings.

CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473400
Diam. intérieur	14.29 mm
Diam. extérieur	25.63 mm
Épaisseur	15.88 mm
Poids	150 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE