


# Accessoire de palier 7613-DL-NICE - 7613-DL-NICE

<https://www.123roulement.be/roulement-palier/paliers/accessoires/7613-dl-nice>

**7600 Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring NICE™**



**PRECISION ENGINEERED FOR ALL CONTACT SURFACES - FINISHED TO THE TIGHTEST TOLERANCES**

- EASY TO USE INCH DIMENSIONS
- MEDIUM LOAD
- MAX SPEED RANGE - 5000 - 8000 RPM
- TIMOTHY HARDENED
- STEEL BEARING
- STYLISH CASE STANDARD
- SHOULD BE OILED
- EASILY APPLICABLE SINGLE LIP CONTACT
- AVAILABLE SINGLE BEARING OR OPEN
- EXTENDED INNER RING WITH SET SCREWS
- ALL BEARINGS HAVE A SHIP FUL CRANK - THIS WILL CHANGE TO AN OPTION
- INDICATED FOR APPLICATIONS WHERE SPECIAL SEALING AND FINISHES ARE REQUIRED.

BEARING	PRINCIPLE DIMENSIONS					
	BORE d (in) (mm)	O.D. D (in) (mm)	WIDTH B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7613™	.8125 20.64	2.0000 50.80	0.8250 20.95	0.0625 1.58	1.306 33.17	0.138 3.45

PRINCIPLE DIMENSIONS						BASIC LOAD RATINGS		WEIGHT	
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N 2 set screws	Radius R (in) (mm)	C Dynamic (lbf) (N)	C <sub>0</sub> Static (lbf) (N)	W (kg)
0.042 1.07	2.156 54.77	1.179 29.95	0.482 12.50	0.261 6.63	1/4-28	0.036 0.89	2970 13217	1360 6008	0.45 0.20

When ordering please indicate designation and style letters of bearing desired (i.e. DL or DLG)      Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
Tolerance for 7613™ and larger is +.0000-.0006 (+.0000-.015)      Weights given are for greased and sealed versions  
All bearing designations listed herein are trademarks of RBC Nide® Bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473448
Diam. intérieur	20.64 mm
Diam. extérieur	33.17 mm
Épaisseur	15.88 mm
Poids	200 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE