

## Accessoire de palier 7620-DL-NICE - 7620-DL-NICE

<https://www.123roulement.be/roulement-palier/paliers/accessoires/7620-dl-nice>

**7600** Series™ Heavy Duty Precision Ground Radial Bearings with Extended Inner Ring (con't)

- PRECISION GRINDING ON ALL CONTACT SURFACES
- EASY TO USE HIGH DIMENSIONS
- MEDIUM LOADS
- MAX. SPEED RANGE: 5000 - 8000 RPM
- THROUGH HOLES
- SHAFER CASE STANDARD
- HEAVY DUTY BEARING
- HEAVY DUTY BEARING
- AVAILABLE SINGLE RINGS OR OPEN
- EXTENDED INNER RING WITH KEY GROOVES
- ALL DIMENSIONS HAVE A SHARP EDGE FINISH, WITH PEEK DIMENSIONS AS AN OPTION
- RECOMMENDED FOR APPLICATIONS WHERE CORROSION RESISTANCE IS REQUIRED

**NICE**

BEARING	PRINCIPLE DIMENSIONS					
	BORE		O.D.		WIDTH	
	d (in) (mm)	D (in) (mm)	B (in) (mm)	A (in) (mm)	F (in) (mm)	G (in) (mm)
7620™	+0.0008 +0.000 -0.0000 -0.000	+0.0000 +0.000 -0.0005 -0.013	+0.000 +0.000 -0.005 -0.13	0.0625 1.59	1.672 42.47	0.190 4.83

PRINCIPLE DIMENSIONS											BASIC LOAD RATINGS		WEIGHT
H (in) (mm)	J (in) (mm)	K (in) (mm)	L (in) (mm)	M (in) (mm)	N (in) (mm)	Radius R (in) (mm)	Dynamic C (lb) (N)	Static C <sub>0</sub> (lb) (N)	W (lb) (kg)				
0.065 1.65	2.768 70.25	1.417 35.98	0.605 15.37	0.261 6.63	1/4-28	0.035 0.89	5360 23852	2620 11659	0.71 0.32				

① When ordering please indicate bearing designation and style letters of bearing desired (i.e. DL or DLG)  
 ② Tolerance for 7613™ and larger is +0.0001-0.0006 (+0.0001-0.015)  
 ③ Radius R indicates the maximum fillet radius in housing or shaft which bearing will clear  
 ④ Weights given are for greased and sealed versions  
 All bearing designations listed herein are trademarks of RBC Nice® Bearings.

## CARACTÉRISTIQUES PRODUIT

Marque	NICE
N° Ean13	3616060473509
Diam. intérieur	31.75 mm
Diam. intérieur	1 1/4" inch
Diam. extérieur	42.47 mm
Diam. extérieur	1.672" inch
Epaisseur	19.05 mm
Epaisseur	3/4" inch
Poids	320 g
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE