

Rotule TSM MSX-M20-DUNLOP - MSX-M20-DUNLOP

<https://www.123roulement.be/roulement-palier/rotule/tsm/msx-m20-dunlop>

MALE ROD ENDS DUNLOP



DUNLOP MSX SERIES
MALE ROD ENDS

Description:
MSX series is our 3-piece steel on steel high strength range of male rod ends designed for motorsport and heavy industrial mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the inner race, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, heat treated, zinc plated and clear trivalent passivate. Inner Ring: Steel 070M20, zinc plated and clear trivalent passivate and stainless steel 304. Liner: High strength PTFE bronze mesh composite. Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes. Low friction, high shock loads. Extended wear life. No maintenance. Studded and stainless steel options.

Possible Applications:
Medium/heavy industrial/mechanical applications. Construction equipment. Agricultural equipment. Motor sport and recreational vehicles requiring high precision motion control.

Temperature Range:
-200°C to +260°C

Specification:
ISO & JIS compliant

Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate

Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate

Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

Liner: High Strength PTFE Composite

Temp Range: -200°C to +260°C

Part No. Right Hand	Part No. Left Hand	Bore size	Thread	W	H	D	L1	L2	Static Load Rating (Newtons) Radial
MSX-M20		20	M20x2.50	25	18.00	50	78	47	93500

Interchange table

Dunlop	Aurora	Fluro
MSX MS-M (metric)	AM-M-T and AB-M-T	GAXSW
MSX MS (imperial)	AM-T and AB-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060550286
Diam. intérieur	20 mm
Diam. extérieur	25 mm
Épaisseur	18 mm
Type	TSM
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE