

# Rotule SI FSL-12-10-F-DUNLOP - FSL-12-10-F-DUNLOP

<https://www.123roulement.be/roulement-palier/rotule/si/fsl-12-10-f-dunlop>

FEMALE ROD ENDS



**FS SERIES: FS - FSS - FS SS**

**DESCRIPTION:**  
FS Series is our 3-piece steel on steel range of male rod ends incorporating a high strength PTFE bronze mesh between the ball and the lower material, suitable for high shock loads and medium to heavy mechanical load applications requiring low friction, available in both metric and imperial bore thread sizes, they do not require maintenance.

**MATERIAL SPECIFICATIONS:**  
Housing: Steel Z30M07Pb and forged 680M46, zinc plated and clear treatment passivate and stainless steel 302L and forged 304, Inner Ring: Steel 620M20 zinc plated and clear treatment passivate, Liner: High strength PTFE bronze mesh composite, Ball: Bearing steel 100Cr6, heat treated, polished & electroless nickel plated and stainless steel 440C.

**FEATURES:**  
Metric & imperial thread & bore sizes, low friction, high shock loads, Extended wear life, No maintenance, Studded and stainless steel options.

**POSSIBLE APPLICATIONS:**  
Medium heavy industrial, mechanical applications, Construction equipment, Agricultural equipment, Motor sport and recreational vehicles requiring high precision motion control.

**TEMPERATURE RANGE:**  
-200°C to +250°C

**SPECIFICATION:**  
ELV & RoHS compliant

**Housing:** Steel Z30M07Pb, Steel 04 - 07 Forged 680M46, Steel 09 - 12 Zinc Plated and Clear Treatment Passivate

**Inner Ring:** Steel 620M20, Zinc Plated and Clear Treatment Passivate

**Ball:** Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated

**Liner:** High Strength PTFE Composite

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	O	AF	Static Load Rating (Newtons) Radial
FSL-12-10F	S/B	3/4 BSF	0.875	0.687	2.000	2.875	1.750	24.80	1.000		45,000

**Interchange table**

Dunlop	Rose	Aurora	Askubal	SKF	Asahi	IKO	Fluro
FS-M (metric)	MFC	MW-M-T and MG-M-T	KI-P	SKR-F	JAF-EC	PHS-EC	QISW
FS (imperial)	RFC	MW-T and MG-T	-	-	PHSB-EC	-	-

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060554628
Diam. intérieur	15.87 mm
Diam. intérieur	0.625" inch
Diam. extérieur	0.875 mm
Diam. extérieur	0.034" inch
Epaisseur	0.687 mm
Epaisseur	0.027" inch
Type	SI
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE