

# Rotule SI

## FX-10-FG-DUNLOP - FX-10-FG-DUNLOP

<https://www.123roulement.be/roulement-palier/rotule/si/fx-10-fg-dunlop>

FEMALE ROD ENDS



**FX SERIES**

**Description:**  
FX series Rod Ends have been developed for use in General Engineering applications where medium to high loads are encountered. Within their load carrying capacity they will withstand shock loading and high frequency oscillation.

**Material Specifications:**  
Housing: B7M 4.0, heat treated to 80/90 tons/m<sup>2</sup> tensile, Phosphated all over. Ball: 100Cr 6, heat treated, Phosphated all over.

**Features:**  
Metric and Imperial sizes available  
Can be used in application involving shock loading and high frequency oscillation.

**Possible Applications:**  
Medium / heavy industrial/mechanical applications  
Construction equipment  
Agricultural equipment and motor sport.

**Temperature Range:**  
-40°C to +150°C

**Specification:**  
ELV & RoHS compliant

Housing: Forged B7M4.0, heat treated to 80/90 tons/m<sup>2</sup> tensile and phosphated all over. Ball: Bearing Steel 100Cr6, Heat Treated and Phosphated all over.

Part No. Right Hand	Part No. Left Hand	D	W	H	O	D	F	A	J	M	X	Static Load Rating (Newton) Radial
FX-10FG		6250	875	750	875	1.937	2.625	1.375	1.000	5/8 BSF	.21	77470

**Interchange table**

Dunlop	Rose	NMB
FX-M (Metric)	RBJ-M	RBJ-M
FX (Imperial)	RBJ	RBJ

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

## CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060555298
Diam. intérieur	6250 mm
Diam. extérieur	875 mm
Épaisseur	750 mm
Type	SI
Filetage	Filetage à droite
Lubrification	avec
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE