

## Rotule SI FSX-06-DUNLOP - FSX-06-DUNLOP

<https://www.123roulement.be/roulement-palier/rotule/si/fsx-06-dunlop>

FEMALE ROD ENDS



**DUNLOP**  
FEMALE ROD ENDS  
**FSX SERIES**

**Description:**  
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

**Material Specifications:**  
Housing: Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate  
Inner Ring: Steel 070M20, Zinc Plated and Clear Trivalent Passivate  
Ball: Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated  
Liner: High Strength PTFE Composite

**Features:**  
Metric & Imperial thread & bore sizes, low friction, heavy duty high shock loads, extended wear life, no maintenance.

**Temperature Range:**  
-200°C to +240°C

**Possible Applications:**  
Motorsport and heavy industrial mechanical applications.

**Specification:**  
ELV & RoHS compliant

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSX-06		3/8	3/8 UNF	0.500	0.406	1.125	1.625	0.937	0.542	34800

**Interchange table**

Dunlop	Aurora	Fluro
FSX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

### CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060556349
Diam. intérieur	9.525 mm
Diam. extérieur	28.575 mm
Epaisseur	12.7 mm
Type	SI
Filetage	Filetage à droite
Lubrification	NA
Charge statique	34.8 kN
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE