

Rotule GE GE12-ES-2RS-DUNLOP - GE12-ES-2RS-DUNLOP

<https://www.123roulement.be/roulement-palier/rotule/ge/ge12-es-2rs-dunlop>

SPHERICAL BEARINGS 



GE ES SERIES

Description:
GE ES-Series is our 2-piece fractured outer ring metric range of spherical plain bearings used in non rotational applications. Ball and race riding surfaces are treated with MoS₂ for increased lubricity on wear surface. A lubrication groove is provided on the raceway for applications requiring re-lubrication after installation.

Material Specifications:
Outer ring: Bearing steel 100Cr6, case hardened and manganese phosphated, treated with MoS₂. Ball: Bearing steel 100Cr6, case hardened and manganese phosphated. Seals: Polyurethane.

Features:
Metric bore sizes
Low cost
Maintenance required
Up to 140mm bore sizes available

Possible Applications:
Light to heavy industrial mechanical applications
Construction equipment
Agricultural equipment
hydraulic applications

Temperature Range:
-24°C to +121°C

Specifications:
ELV & RoHS compliant

Outer Ring: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate, wear faces treated with MoS₂.

Ball: Bearing Steel 100Cr6, Case Hardened and Manganese Phosphate

Seals: Polyurethane

Part No. Unsealed	Part No. Sealed	Bore Size	W	H	D	Static Load Rating (Newtons) Radial
	GE12ES-2RS	12	10	7	22	94,000



CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060557469
Diam. intérieur	12 mm
Diam. intérieur	0.472" inch
Diam. extérieur	22 mm
Diam. extérieur	0.866" inch
Epaisseur	10 mm
Epaisseur	0.394" inch
Type	GE
Lubrification	avec
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE