

Rotule SA FSLX-M08-6-DUNLOP - FSLX-M08-6-DUNLOP

<https://www.123roulement.be/roulement-palier/rotule/sa/fslx-m08-6-dunlop>

FEMALE ROD ENDS 



FSX SERIES

Description:
FSX series is our 3-piece steel on steel high strength range of female rod ends designed for motorsport and heavy industrial, mechanical load applications. Incorporating a high strength PTFE bronze mesh between the ball and the liner material, suitable for high shock loads and heavy mechanical load applications requiring low friction, available in both metric and imperial bore and thread sizes, they do not require maintenance.

Material Specifications:
Housing: Steel 708M40, heat treated, zinc plated and clear trivalent passivate
Inner Ring: Steel 670M20, zinc plated and clear trivalent passivate and stainless steel 304C. Liner: High strength PTFE bronze mesh composite.
Ball: 100Cr6 heat treated, polished and electroless Nickel plated and stainless steel 440C.

Features:
Metric & imperial thread & bore sizes, low friction, heavy duty, high shock loads, extended wear life, no maintenance.

Isolated option

Temperature Range:
-200°C to +240°C

Possible Applications:
Motorsport and heavy industrial mechanical applications.

Specification:
ELV & RoHS compliant

Housing:	Steel 708M40, Heat Treated, Zinc Plated and Clear Trivalent Passivate	Balls:	Bearing Steel 100Cr6, Case Hardened and Electro-less Nickel Plated
Inner Ring:	Steel 670M20, Zinc Plated and Clear Trivalent Passivate	Liners:	High Strength PTFE Composite
		Temp Range:	-200°C to +240°C

Part No. Right Hand	Part No. Left Hand	Bore Size	Thread	W	H	D	L1	L2	AF	Static Load Rating (Newtons) Radial
FSLX-M08-6		6	M8x1.25	12	9.00	24	26	16	13	25500

Interchange table

Dunlop	Aurora	Fluro
FSLX-M (Metric)	AM-M-T and AD-M-T	GUSW
FSLX (Imperial)	AM-T and AD-T	

Note: Manufacturers part numbers are used for descriptive purposes only and may not be direct equivalent products.

CARACTÉRISTIQUES PRODUIT

Marque	DUNLOP
N° Ean13	3616060558800
Diam. intérieur	6 mm
Diam. intérieur	0.236" inch
Diam. extérieur	24 mm
Diam. extérieur	0.945" inch
Epaisseur	12 mm
Epaisseur	0.472" inch
Type	SA
Filetage	Filetage à gauche
Lubrification	NA
Charge statique	25.5 kN
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE