


Rondelle ondulée fendue

SWSW-85.73-72.14-0.76-4-SS - SWSW-85.73-72.14-0.76-4-SS

<https://www.123roulement.be/accessoire/rondelle/rondelle-ondulee-fendue/sws-85.73-72.14-0.76-4-ss>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (+/-15 % Newton)
DBo = Bearing's outside diameter
Db = Free fit in hole diameter
De = Free fit over hole diameter
N = Number of waves



Split Wave Spring Washers

| Part Number | Di (mm) | t (mm) | L1 (N) | H1 (mm) | Do (mm) | N | H (mm) |
|----------------|---------|--------|--------|---------|---------|---|--------|
| WWG0337022056S | 72.14 | 0.76 | 249.1 | 2.769 | 85.73 | 4 | 5.59 |

CARACTÉRISTIQUES PRODUIT

| | |
|--------------------------|----------|
| Marque | GEN |
| Diam. intérieur | 72.14 mm |
| Epaisseur | 0.76 mm |
| Matière | INOX |
| Conditionnement | 1 |
| Charge à L1 | 249.1 N |
| Charge en hauteur | 2.769 |
| Diamètre extérieur (max) | 85.73 mm |
| Nombre d'ondes | 4 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE