


Rondelle ondulée fendue

SWSW-304.80-283.46-0.81-9-SS - SWSW-304.80-283.46-0.81-9-SS

<https://www.123roulement.be/accessoire/rondelle/rondelle-ondulee-fendue/sws-304.80-283.46-0.81-9-ss>

Do = Outside diameter (max) (mm)
Di = Inside diameter (min) (mm)
t = Thickness (mm)
H = Free height approx.
H1 = Load at height
L1 = Load at L1 (+/-15 % Newton)
DB = Bearing's outside diameter
Dh = Free fit in hole diameter
Dr = Free fit over hole diameter
N = Number of waves



Split Wave Spring Washers

Part Number	Di (mm)	t (mm)	L1 (N)	H1 (mm)	Do (mm)	N	H (mm)
WWG1200044082S	283,46	0,81	809,576	3,962	304,80	9	11,18

CARACTÉRISTIQUES PRODUIT

Marque	GEN
Diam. intérieur	283.46 mm
Epaisseur	0.81 mm
Matière	INOX
Conditionnement	1
Charge à L1	809.576 N
Charge en hauteur	3.962
Diamètre extérieur (max)	304.8 mm
Nombre d'ondes	9

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE