


Roulement conique NN3014-K-NTN - NN3014-K-NTN

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/nn3014-k-ntn>



Double Row Cylindrical Roller Bearing w/ Tapered Bore - Type NK - Dimensions

Technical Specifications		Imperial Specifications	
Type	Cylindrical Roller Bearing		2.7558 in 70.000 mm
Bore Type	Tapered	D	4.3307 in 110.000 mm
Material	Hardened Alloy Steel	B	1.1811 in 30.000 mm
Cage Material	High Strength, 2 piece, Polished Brass	C	1.1811 in 30.000 mm
Limiting Speed - Oil	6900 RPM	Ew	3.9370 in 100.000 mm
Limiting Speed - Grease	5800 RPM	r	0.0433 in 1.100 mm
Taper	1:50	da min	3.0118 in 76.500 mm
Precision	ISO Class 0	db min	3.1102 in 79.000 mm
Configuration	Flange	Da max	3.9764 in 101.000 mm
Oil Hole	w/o Oil Hole	Db min	3.9764 in 101.000 mm
Radial Internal Clearance	CN	Db max	4.0748 in 103.500 mm
Static Load Rating	32000 lbf 143200 N 143.00 kN	rsa max	0.0394 in 1.000 mm
Dynamic Load Rating	31200 lbf 14000 N 14.00 kN		
Enclosure	Open		
Operating Temperature Range	-40 to 250 °F -40 to 120 °C		

CARACTÉRISTIQUES PRODUIT

Marque	NTN
N° Ean13	3616060804792
Diam. intérieur	70 mm
Diam. extérieur	110 mm
Épaisseur	30 mm
Charge dynamique	94.5 kN
Charge statique	143 kN
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE