

Pâte à joint

MR-5922-200ML-LOCTITE - MR-5922-200ML-LOCTITE

<https://www.123roulement.be/lubrifiant-adhesif/adhesif/pateajoint/mr-5922-200ml-loctite>

TITRE	Résine
DESCRIPTION	Pâte d'étanchéité souple (ex FAG n°2)
NOM	LOCTITE MR 5922
CONDITIONNEMENT	Tube 200 ml
COMMENTAIRE	
APPROBATION*	

Description

LOCTITE® MR 5922 is a black, viscous, solvent-based, slow drying, flexible setting paste that changes to a pliable, non-hardening film through solvent evaporation. It is based on resin, isopropanol and fillers. It seals flanges, fittings, connections and flexible assemblies against leakage. It increases the reliability of gasket seals and it can be used for the repair of damaged pre-cut gaskets.

Avantages

Extends gasket life
Prevents leaks
Slow drying
Flexible setting
Specifically designed to improve the sealing performance of pre-formed gaskets made of cork, metal, plastic, rubber, etc. in non-rigid assemblies
Increases the reliability of gasket seals

Caractéristiques

Flexible sealant paste that changes to a pliable, non-hardening film through solvent evaporation which seals flanges, fittings, connections, etc.

CARACTÉRISTIQUES PRODUIT

Marque	LOCTITE
N° Ean13	5010266188645
Poids	341 g
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE