


## Roulement conique 32203-JR-JTEKT - 32203-JR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/32203-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>		
d	D	T	B	C	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.					
17	40	17.25	16	14	1	27.4	27.5	10 000	14 000			32203JR		
Dimension series to ISO 995 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>1</sub> min.	d <sub>2</sub> max.	D <sub>1</sub> max.	D <sub>2</sub> min.	S <sub>1</sub> min.	S <sub>2</sub> min.	r <sub>1</sub> max.	r <sub>2</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
20D	11.4	22.5	23	34.5	33	37	2	3	1	1	0.31	1.92	1.06	0.104

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952398013
Diam. intérieur	17 mm
Diam. intérieur	0.669" inch
Diam. extérieur	40 mm
Diam. extérieur	1.575" inch
Epaisseur	17.25 mm
Epaisseur	0.679" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE