

Roulement conique 303-22-XR-JTEKT - 303-22-XR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/303-22-xr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
22	56	17.25	16	13	36.3	36.6	7 700	10 000	303/22XR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S ₁ min.	S ₂ min.		r ₁ max.	r ₂ max.		Y ₁	Y ₀	
—	15.7	30.5	31	47.5	44	52	3	4	1.5	1.5	0.59	1.02	0.56	0.210

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400440
Diam. intérieur	22 mm
Diam. extérieur	56 mm
Épaisseur	17.25 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE