


Roulement conique 32306-CR-JTEKT - 32306-CR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/32306-cr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾	
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.		
30	72	28.75	27	23	1.5	1.5	80.0	93.8	6 000	8 000	32306CR	
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)	
5FD	22.0	d ₁ min.	d ₂ max.	D ₁ max.	D ₂ min.	S ₁ min.	S ₂ min.	r ₁ max.	r ₂ max.	Y ₁	Y ₀	0.610
		38.5	37	63.5	54	68	3	5.5	1.5	1.5	1.10	0.60

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400754
Diam. intérieur	30 mm
Diam. extérieur	72 mm
Épaisseur	28.75 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE