

## Roulement conique 302-32-R-JTEKT - 302-32-R-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/302-32-r-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
32	65	18.25	17	15	1	1	48.0	51.4	6 200	8 200	302/32R			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>α</sub> min.	d <sub>α</sub> max.	D <sub>α</sub> min.	D <sub>α</sub> max.	S <sub>α</sub> min.	S <sub>α</sub> max.	r <sub>α</sub> min.	r <sub>α</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
—	14.9	37.5	39	59.5	55	61	3	3	1	1	0.37	1.60	0.88	0.286

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952400785
Diam. intérieur	32 mm
Diam. extérieur	65 mm
Épaisseur	18.25 mm
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE