

Roulement conique T5ED060-JTEKT - T5ED060-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/t5ed060-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾
d	D	T	B	C	C _r	C _{0r}	C ₉₀	C ₁₀₀	Grease lub.	Oil lub.	
60	115	39	38	31	158	227	3 400	4 600	T5ED060		

Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.		Y ₁	Y ₀		
5ED	32.4	78	70	103	92	110	5	8	3	2	0.53	1.13	0.62	1.81

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952406015
Diam. intérieur	60 mm
Diam. intérieur	2.362" inch
Diam. extérieur	115 mm
Diam. extérieur	4.528" inch
Epaisseur	39 mm
Epaisseur	1.535" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE