

Roulement conique 30315-DJR-JTEKT - 30315-DJR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/30315-djr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
75	160	40	37	26	213	254	2 100	2 900	30315DJR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _α min.	d _β max.	D _α max.	D _β min.	S _α min.	S _β min.		r _α max.	r _β max.		Y ₁	Y ₀	
7GB	49.9	89	91	148	127	151	6	14	2.5	2	0.83	0.73	0.40	3.45

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952409290
Diam. intérieur	75 mm
Diam. intérieur	2.953" inch
Diam. extérieur	160 mm
Diam. extérieur	6.299" inch
Epaisseur	40 mm
Epaisseur	1.575" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE