

Roulement conique 30316-JR-JTEKT - 30316-JR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/30316-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)				Limiting speeds (min ⁻¹)		Bearing No. ¹⁾		
d	D	T	B	C	r ₁ min.	C _r	C _{0r}	Grease lub.	Oil lub.					
80	170	42.5	39	33	3	2.5	294	355	2 300	3 100	30316JR			
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d _α min.	d _α max.	D _α min.	D _α max.	S _α min.	S _α max.	r _α min.	r _α max.		Y ₁	Y ₀		
2GB	34.8	94	102	158	148	159	4	9.5	2.5	2	0.35	1.74	0.96	4.46

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122224
Diam. intérieur	80 mm
Diam. intérieur	3.15" inch
Diam. extérieur	170 mm
Diam. extérieur	6.693" inch
Epaisseur	42.5 mm
Epaisseur	1.673" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE