

Roulement conique T2ED080-JTEKT - T2ED080-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/t2ed080-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
80	145	46	45	38	3	2.5	266	381	2 600 3 500	T2ED080				
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)						Constant e	Axial load factors		(Refer. 1) Mass (kg)			
		d _α min.	d _α max.	D _α min.	D _α max.	S _α min.	S _α max.		r _α min.	r _α max.		Y ₁	Y ₀	
2ED	32.7	94	92	133	125	137	7	8	2.5	2	0.32	1.88	1.03	3.20

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952409566
Diam. intérieur	80 mm
Diam. extérieur	145 mm
Épaisseur	46 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE