


## Roulement conique 30319-DJR-JTEKT - 30319-DJR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/30319-djr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>90</sub>	C <sub>100</sub>	Grease lub.	Oil lub.				
95	200	49.5	45	32	4	3	319	391	1 700	2 300	30319DJR			
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1</sub> min.	d <sub>1</sub> max.	D <sub>1</sub> min.	D <sub>1</sub> max.	S <sub>1</sub> min.	S <sub>1</sub> max.	r <sub>1</sub> min.	r <sub>1</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
7GB	62.7	113	113	186	157	187	6	17.5	3	2.5	0.83	0.73	0.40	6.68

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250122378
Diam. intérieur	95 mm
Diam. extérieur	200 mm
Épaisseur	49.5 mm
Conditionnement	-

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE