

## Roulement conique 32956-JR-JTEKT - 32956-JR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/32956-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)						Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>				
d	D	T	B	C	r <sub>1</sub> min.	C <sub>r</sub>	C <sub>0r</sub>	Grease lub.	Oil lub.					
280	380	63.5	63.5	48	3	2.5	780	1630	770	1000	32956JR			
Dimension series to ISO355 (Refer.)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer.) Mass (kg)	
		d <sub>α</sub> min.	d <sub>β</sub> max.	D <sub>α</sub> max.	D <sub>β</sub> min.	S <sub>α</sub> min.	S <sub>β</sub> min.	r <sub>α</sub> max.	r <sub>β</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
4EC	75.1	294	298	368	347	368	11	15.5	2.5	2	0.43	1.39	0.76	20.14

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250125812
Diam. intérieur	280 mm
Diam. intérieur	11.024" inch
Diam. extérieur	380 mm
Diam. extérieur	14.961" inch
Epaisseur	63.5 mm
Epaisseur	2 1/2" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE