

## Roulement conique 32926-JR-JTEKT - 32926-JR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/32926-jr-jtekt>

Single-row tapered roller bearings  
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)				Limiting speeds (min <sup>-1</sup> )		Bearing No. <sup>1)</sup>			
d	D	T	B	C	C <sub>r</sub>	C <sub>0r</sub>	C <sub>0e</sub>	C <sub>0e</sub>	Grease lub.	Oil lub.				
130	180	32	32	25	2	1.5	200	368	1 900	2 500	32926JR			
Dimension series to ISO355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)								Constant e	Axial load factors		(Refer. 1) Mass (kg)	
		d <sub>1a</sub> min.	d <sub>1a</sub> max.	D <sub>1a</sub> min.	D <sub>1a</sub> max.	S <sub>1a</sub> min.	S <sub>1a</sub> max.	r <sub>1a</sub> min.	r <sub>1a</sub> max.		Y <sub>1</sub>	Y <sub>0</sub>		
20C	31.4	140	141	171	165	174	6	7	2	1.5	0.34	1.77	0.97	2.42

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	4549250125669
Diam. intérieur	130 mm
Diam. intérieur	5.118" inch
Diam. extérieur	180 mm
Diam. extérieur	7.087" inch
Epaisseur	32 mm
Epaisseur	1.26" inch
Conditionnement	1
Norme	Sans norme

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE