

Roulement conique 33030-JR-JTEKT - 33030-JR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/33030-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



| Boundary dimensions (mm) | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | | Bearing No. ¹⁾ | | | | | |
|--|--------------------|--------------------------|---------------------|---------------------|-------------------------|---------------------|--------------------------------------|---------------------|---------------------------|------------|-----------------------------------|-----------------------------------|----------------------|------|
| d | D | T | B | C | C _r | C _{0r} | Grease lub. | Oil lub. | | | | | | |
| 150 | 225 | 59 | 59 | 46 | 459 | 869 | 1 500 | 2 000 | 33030JR | | | | | |
| Dimension series to ISO 355 (Refer. 1) | Load center (mm) a | Mounting dimensions (mm) | | | | | | | | | | | | |
| | | d _α min. | d _α max. | D _α min. | D _α max. | S _α min. | S _α max. | r _α min. | r _α max. | Constant e | Axial load factors Y ₁ | Axial load factors Y ₀ | (Refer. 1) Mass (kg) | |
| 2EE | 47.8 | 164 | 164 | 213 | 200 | 217 | 8 | 13 | 2.5 | 2 | 0.36 | 1.65 | 0.90 | 8.09 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 4549250126130 |
| Diam. intérieur | 150 mm |
| Diam. extérieur | 225 mm |
| Epaisseur | 59 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE