

Roulement conique 30334-JR-JTEKT - 30334-JR-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/30334-jr-jtekt>

Single-row tapered roller bearings
metric series

Koyo



Boundary dimensions (mm)					Basic load ratings (kN)		Limiting speeds (min ⁻¹)		Bearing No. ¹⁾					
d	D	T	B	C	C _r	C _{0r}	Grease lub.	Oil lub.						
170	360	80	72	62	1 040	1 370	1 000	1 300	30334JR					
Dimension series to ISO 355 (Refer. 1)	Load center (mm) a	Mounting dimensions (mm)												
		d _{1a} min.	d _{1a} max.	D _{1a} min.	D _{1a} max.	S _{1a} min.	S _{1a} max.	r _{1a} min.	r _{1a} max.	Constant e	Axial load factors Y ₁	Axial load factors Y ₀	(Refer. 1) Mass (kg)	
2GB	67.9	192	218	342	306	329	13	18	4	3	0.35	1.74	0.96	37.5

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952421346
Diam. intérieur	170 mm
Diam. extérieur	360 mm
Épaisseur	80 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE