


Roulement conique

HM88630-HM88610-JTEKT - HM88630-HM88610-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/hm88630-hm88610-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ _{min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
25.400	72.233	25.400	25.400	19.842	0.8	2.4	86.9	87.4	5 700	7 600

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a _{max.}	<i>r</i> _b _{max.}	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
HM88630	HM88610	20.7	39.5	39.5	60.0	69.0	0.8	2.4	0.55	1.10	0.60	0.391	0.185

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952425733
Diam. intérieur	25.4 mm
Diam. intérieur	1" inch
Diam. extérieur	72.233 mm
Diam. extérieur	2 27/32" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE