

Roulement conique 02878-02820-JTEKT - 02878-02820-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/02878-02820-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|---------------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ _{min.} | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 34.925 | 73.025 | 22.225 | 22.225 | 17.462 | 0.8 | 3.2 | 55.0 | 65.7 | 5 500 | 7 400 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|---------------------------------------|---------------------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a _{max.} | <i>r</i> _b _{max.} | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 02878 | 02820 | 18.4 | 42.5 | 42.0 | 62.0 | 68.0 | 0.8 | 3.2 | 0.45 | 1.32 | 0.73 | 0.265 | 0.158 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952426334 |
| Diam. intérieur | 34.925 mm |
| Diam. extérieur | 43.025 mm |
| Épaisseur | 22.225 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE