


Roulement conique 449-432-JTEKT - 449-432-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/449-432-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|----------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> _{1 min.} | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 34.925 | 95.250 | 27.783 | 29.901 | 22.225 | 0.8 | 2.4 | 103 | 122 | 4 500 | 5 900 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|----------------------------|----------------------------|----------|-----------------------|-----------------------|--------------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 449 | 432 | 18.4 | 44.0 | 43.5 | 83.0 | 87.0 | 0.8 | 2.4 | 0.28 | 2.11 | 1.16 | 0.686 | 0.384 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952426396 |
| Diam. intérieur | 34.925 mm |
| Diam. extérieur | 95.25 mm |
| Épaisseur | 27.783 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE