


Roulement conique 2788R-2735X-JTEKT - 2788R-2735X-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/2788r-2735x-jtekt>

Single-row tapered roller bearings
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
38.100	73.025	23.812	25.654	19.050	3.6	0.8	74.1	92.2	5 400	7 200

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.		<i>Y</i> ₁	<i>Y</i> ₂		Inner ring
2788R	2735X	15.9	50.0	43.5	66.0	69.0	3.6	0.8	0.30	1.98	1.09	0.308	0.134

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952426600
Diam. intérieur	38.1 mm
Diam. intérieur	1 1/2" inch
Diam. extérieur	73.025 mm
Diam. extérieur	2 7/8" inch
Epaisseur	23.812 mm
Epaisseur	15/16" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE