

Roulement conique 27880-27820-JTEKT - 27880-27820-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/27880-27820-jtekt>

Single-row tapered roller bearings
inch series Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|---------------------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ _{max.} | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 38.100 | 80.035 | 24.608 | 23.698 | 18.512 | 0.8 | 1.6 | 73.2 | 91.6 | 5 200 | 6 900 |

| Bearing No. | | Load center (mm) <i>a</i> | Mounting dimensions (mm) | | | | | | Constant <i>e</i> | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------------------|--------------------------|-----------------------|-----------------------|-----------------------|---------------------------------------|---------------------------------------|----------------------|-----------------------|-----------------------|-----------------------|------------|
| Inner ring | Outer ring | | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a _{max.} | <i>r</i> _b _{max.} | | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 27880 | 27820 | 22.2 | 48.0 | 47.0 | 68.0 | 75.0 | 0.8 | 1.6 | 0.56 | 1.07 | 0.59 | 0.378 | 0.208 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952426631 |
| Diam. intérieur | 38.1 mm |
| Diam. extérieur | 80.035 mm |
| Épaisseur | 24.608 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE