


## Roulement conique 46162-46368-JTEKT - 46162-46368-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/46162-46368-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
41.275	93.662	31.750	31.750	26.195	0.8	3.2	105	134	4 400	5 800

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.		<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
46162	46368	24.0	52.0	51.0	79.0	87.0	0.8	3.2	0.40	1.49	0.82	0.695	0.403

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952426921
Diam. intérieur	41.275 mm
Diam. intérieur	1 5/8" inch
Diam. extérieur	93.662 mm
Diam. extérieur	3 11/16" inch
Epaisseur	31.75 mm
Epaisseur	1 1/4" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE