


## Roulement conique

### HM807035-HM807010-JTEKT - HM807035-HM807010-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/hm807035-hm807010-jtekt>

Single-row tapered roller bearings  
inch series Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
41.275	104.775	36.512	36.512	28.575	1.6	3.2	141	195	3 800	5 100

Bearing No.		Load center (mm) <i>a</i>	Mounting dimensions (mm)						Constant <i>e</i>	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring		<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.		<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
HM807035	HM807010	29.3	60.0	57.0	89.0	100.0	1.6	3.2	0.49	1.23	0.68	1.19	0.497

## CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952426952
Diam. intérieur	41.275 mm
Diam. intérieur	1 5/8" inch
Diam. extérieur	104.775 mm
Diam. extérieur	4 1/8" inch
Epaisseur	36.512 mm
Epaisseur	1 7/16" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE