


Roulement conique 369A-362A-JTEKT - 369A-362A-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/369a-362a-jtekt>

Single-row tapered roller bearings
inch series Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|--------|--------|--------|--------|------------------|------------------|-------------------------|-----------------|--------------------------------------|----------|
| d | D | T | B | C | r _{max} | r _{min} | C _r | C ₁₀ | Grease lub. | Oil lub. |
| 47.625 | 88.900 | 20.638 | 22.225 | 16.513 | 3.6 | 1.2 | 74.3 | 87.3 | 4 400 | 5 800 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | |
|-------------|------------|------------------|--------------------------|----------------|----------------|----------------|---------------------|---------------------|----------|--------------------|----------------|--------------------|------------|
| Inner ring | Outer ring | a | d _a | d _b | D _a | D _b | r _s max. | r _s min. | e | Y ₁ | Y ₂ | Inner ring | Outer ring |
| 369A | 362A | 16.1 | 60.0 | 53.0 | 81.0 | 84.0 | 3.6 | 1.2 | 0.32 | 1.88 | 1.03 | 0.373 | 0.164 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952427348 |
| Diam. intérieur | 47.625 mm |
| Diam. extérieur | 88.9 mm |
| Épaisseur | 20.638 mm |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE