

Roulement conique 368S-362A-JTEKT - 368S-362A-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/368s-362a-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> _{1 min.}	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
51.592	88.900	20.638	22.225	16.513	2.0	1.2	74.3	87.3	4 400	5 800

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
368S	362A	16.1	59.0	56.0	81.0	84.0	2.0	1.2	0.32	1.88	1.03	0.321	0.164

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952427829
Diam. intérieur	51.592 mm
Diam. extérieur	88.9 mm
Épaisseur	20.638 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE