

## Roulement conique 539A-532X-JTEKT - 539A-532X-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/539a-532x-jtekt>

Single-row tapered roller bearings  
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min <sup>-1</sup> )	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> <sub>max.</sub>	<i>r</i> <sub>1</sub> min.	<i>C</i> <sub>r</sub>	<i>C</i> <sub>10</sub>	Grease lub.	Oil lub.
53.975	107.950	36.512	36.957	28.575	5.6	3.2	138	172	3 800	5 100

  

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> <sub>a</sub>	<i>d</i> <sub>b</sub>	<i>D</i> <sub>a</sub>	<i>D</i> <sub>b</sub>	<i>r</i> <sub>a</sub> max.	<i>r</i> <sub>b</sub> max.	<i>e</i>	<i>Y</i> <sub>1</sub>	<i>Y</i> <sub>2</sub>	Inner ring	Outer ring
539A	532X	23.9	72.0	61.0	94.0	100.0	5.6	3.2	0.30	2.03	1.11	0.861	0.569

### CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952427898
Diam. intérieur	53.975 mm
Diam. intérieur	2 1/8" inch
Diam. extérieur	107.95 mm
Diam. extérieur	4 1/4" inch
Epaisseur	36.512 mm
Epaisseur	1 7/16" inch
Conditionnement	1

[contact@123roulement.be](mailto:contact@123roulement.be)

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE