



Roulement conique 6386-6320-JTEKT - 6386-6320-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/6386-6320-jtekt>

Single-row tapered roller bearings
inch series 



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
66.675	135.755	53.975	58.007	44.450	4.3	3.2	266	357	3 000	4 000

Bearing No.		Load center (mm)	Mounting dimensions (mm)						Constant	Axial load factors		(Refer.) Mass (kg)	
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
6386	6320	34.8	87.0	77.5	117.0	126.0	4.3	3.2	0.32	1.85	1.02	2.27	1.37

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428666
Diam. intérieur	66.675 mm
Diam. extérieur	135.755 mm
Épaisseur	53.975 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE