

Roulement conique 655-653-JTEKT - 655-653-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/655-653-jtekt>

Single-row tapered roller bearings
inch series

Koyo



| Boundary dimensions (mm) | | | | | | | Basic load ratings (kN) | | Limiting speeds (min ⁻¹) | |
|--------------------------|----------|----------|----------|----------|--------------------------|----------------------------|-------------------------|------------------------|--------------------------------------|----------|
| <i>d</i> | <i>D</i> | <i>T</i> | <i>B</i> | <i>C</i> | <i>r</i> _{max.} | <i>r</i> ₁ min. | <i>C</i> _r | <i>C</i> ₁₀ | Grease lub. | Oil lub. |
| 69.850 | 146.050 | 41.275 | 41.275 | 31.750 | 3.6 | 3.2 | 208 | 301 | 2 600 | 3 400 |

| Bearing No. | | Load center (mm) | Mounting dimensions (mm) | | | | | Constant | Axial load factors | | (Refer.) Mass (kg) | | |
|-------------|------------|------------------|--------------------------|-----------------------|-----------------------|-----------------------|----------------------------|----------------------------|--------------------|-----------------------|-----------------------|------------|------------|
| Inner ring | Outer ring | <i>a</i> | <i>d</i> _a | <i>d</i> _b | <i>D</i> _a | <i>D</i> _b | <i>r</i> _a max. | <i>r</i> _b max. | <i>e</i> | <i>Y</i> ₁ | <i>Y</i> ₂ | Inner ring | Outer ring |
| 655 | 653 | 33.4 | 88.0 | 82.0 | 131.0 | 139.0 | 3.6 | 3.2 | 0.41 | 1.47 | 0.81 | 2.35 | 0.891 |

CARACTÉRISTIQUES PRODUIT

| | |
|-----------------|---------------|
| Marque | JTEKT |
| N° Ean13 | 3663952428857 |
| Diam. intérieur | 69.85 mm |
| Diam. intérieur | 2 3/4" inch |
| Diam. extérieur | 146.05 mm |
| Diam. extérieur | 5 3/4" inch |
| Epaisseur | 41.275 mm |
| Epaisseur | 1 5/8" inch |
| Conditionnement | 1 |

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE