


Roulement conique 567A-563-JTEKT - 567A-563-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/567a-563-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
d	D	T	B	C	r_{max}	r_{min}	C_r	C_{10}	Grease lub.	Oil lub.
71.438	127.000	36.512	36.170	28.575	3.6	3.2	156	226	3 000	4 000

Bearing No.		Load center (mm) a	Mounting dimensions (mm)					Constant e	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring		d_a	d_b	D_a	D_b	r_a max.		r_b max.	Y_1	Y_2	Inner ring	Outer ring
567A	563	28.6	86.0	80.0	112.0	120.0	3.6	3.2	0.36	1.65	0.91	1.19	0.648

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952428901
Diam. intérieur	71.438 mm
Diam. extérieur	127 mm
Épaisseur	36.512 mm
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE