


Roulement conique 27689-27620-JTEKT - 27689-27620-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/27689-27620-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
83.345	125.412	25.400	25.400	19.845	0.8	1.6	101	162	2 900	3 800

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
27689	27620	24.7	90.0	90.0	115.0	120.0	0.8	1.6	0.42	1.44	0.79	0.746	0.344

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952429410
Diam. intérieur	83.345 mm
Diam. intérieur	3.281" inch
Diam. extérieur	125.412 mm
Diam. extérieur	4 15/16" inch
Epaisseur	25.4 mm
Epaisseur	1" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE