


Roulement conique

HH224335-HH224310-JTEKT - HH224335-HH224310-JTEKT

<https://www.123roulement.be/roulement-palier/roulement-rouleaux/conique/hh224335-hh224310-jtekt>

Single-row tapered roller bearings
inch series

Koyo



Boundary dimensions (mm)							Basic load ratings (kN)		Limiting speeds (min ⁻¹)	
<i>d</i>	<i>D</i>	<i>T</i>	<i>B</i>	<i>C</i>	<i>r</i> _{max.}	<i>r</i> ₁ min.	<i>C</i> _r	<i>C</i> ₁₀	Grease lub.	Oil lub.
101.600	212.725	66.675	66.675	53.975	7.1	3.2	513	699	1 800	2 400

Bearing No.		Load center (mm)	Mounting dimensions (mm)					Constant	Axial load factors		(Refer.) Mass (kg)		
Inner ring	Outer ring	<i>a</i>	<i>d</i> _a	<i>d</i> _b	<i>D</i> _a	<i>D</i> _b	<i>r</i> _a max.	<i>r</i> _b max.	<i>e</i>	<i>Y</i> ₁	<i>Y</i> ₂	Inner ring	Outer ring
HH224335	HH224310	47.6	121.0	134.0	189.0	201.0	7.1	3.2	0.33	1.84	1.01	7.76	3.03

CARACTÉRISTIQUES PRODUIT

Marque	JTEKT
N° Ean13	3663952430003
Diam. intérieur	101.6 mm
Diam. intérieur	4" inch
Diam. extérieur	212.725 mm
Diam. extérieur	8 3/8" inch
Epaisseur	66.675 mm
Epaisseur	2 5/8" inch
Conditionnement	1

contact@123roulement.be

02 808 18 02

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE